

The Chronos 1F ISO is designed to perform emission and immunity tests on automotive components. The design of the structure is optimised for maximum performances, in minimum space. The shielding and its pyramidal absorbers are manufactured by SIEPEL.

CHARACTERISTICS

➤ Compliance & Performances

	CISPR 25 & ISO 11452-2	
Measurement distance	1 m	1 m
Frequency range	(150 kHz) 70 MHz - 18 GHz	80 MHz - 18 GHz
Guaranteed performances	Reflectivity < -6 dB	Reflectivity < -10 dB
Compliance	Full-compliant	Full-compliant

**SHIELDING EFFECTIVENESS COMPLIES WITH EN 50147-1
(10 kHz - 18 GHz)**

➤ About our absorbers

- HY absorbers power handling: 2 kW/m² (CW).
- Both absorbers coated with either aqueous or plastic paint are classified ISO class 4 (ISO 14644-1:2015) clean room conditions.

➤ Dimensions (L x W x H)

Total overall including metallic frame	External shield to shield	Internal usable
6.1 x 4.8 x 3.4 m 20 x 16 x 11 ft	6 x 4.8 x 3.3 m 19 x 15 x 11 ft	5.5 x 4.2 x 3 m 18 x 14 x 10 ft

➤ Quality

- All absorbers batches are tested by SIEPEL for reflectivity performances between 30 MHz – 1000 MHz.
- Our raw materials are compliant to RoHS / REACH and free of substances in the current list of Substances of Very High Concern (SVHC) published by the European Chemicals Agency (ECHA).

OUR STRENGTHS

- ⊕ High-quality components & parts
- ⊕ Guarantee of 20 years for the RF performances of our absorbers
- ⊕ Guaranteed performances
- ⊕ Control of performances before shipment
- ⊕ Measurement department accredited ISO/IEC 17025:2005 (accreditation n° 1-6220, scope available on www.cofrac.fr)
- ⊕ Fast delivery: permanent stock available off the shelves
- ⊕ Setting-up of the chambers by our dedicated installation team




CONFIGURATION




MODULAR SHIELDING

Self-standing structure up to 18 (40) GHz
Steele stiffeners



OPTIMISED ABSORBER LINING

Ferrite absorbers (walls and ceiling)
Hybrid truncated absorbers (full lining of walls and ceiling)



DOOR

Manual single leaf swing door
Clearance 1.2 x 2.1 m



TEST TABLE

Dimensions: 2.5 x 1 x 0.9 m with copper strips



WALL PANELS

Penetration panel including coaxial feedthroughs and waveguides



PROJECT REALISATION

Project management
Technical design & study
On-site installation



VENTILATION

Honeycomb air vents
300 x 300 mm up to 18 (40) GHz



PERFORMANCE VERIFICATION

Shielding effectiveness at 900 MHz at critical locations



POWER DISTRIBUTION

Power filter single phase 32 A
Power filter three-phase 32 A
Electrical package : power distribution, lighting

AVAILABLE OPTIONS

- Extended shielding performances up to 40 GHz
- Shielded control and amplifier rooms
- Plastic paint for pyramidal absorbers with wide range of colors
- Other types and dimensions of doors
- Electrically-assisted door latching/unlatching
- Antenna positioners
- Floor hatches with connection points
- Additional power filters, data filters and special feedthroughs
- CCTV / Audio monitoring systems
- Fire detection systems
- On request, some measurements can be accredited ISO 17025 (accreditation number 1-6220, scope available on www.cofrac.fr).
- Military / RadioCom standards compliance
- Many other options on demand

FOR OTHER EMC CHAMBERS
PLEASE REFER TO OUR
DATASHEET
«HOW TO CHOOSE AN
ANECHOIC CHAMBER»

